



SRD SERIES

LED Round Panel Light 3-CCT & 1-CCT Recessed & Surface Type



LED Panel Light
Down Light
1CCT & 3CCT
9W 12W 18W 24W
100-120 Lm/Watt
6000K 4000K 3000K

Amb Tmp: -25-45°C
CRI: Ra>80
Flicker Free Built-in
LED Driver
1.5KV SPD Built-in
Retaining Chain for
Maintenance

Recessed & Surface
Life: 30,000 Hours
PF >0.70
100-240V 50/60Hz
50mm to 200mm
Hole Dia Adaptability
CE & RoHS




Applications:
Shops & Sales Outlets
School Rooms & Office Rooms
Homes & Kitchens
Restaurants & Corridors

False Ceiling & Concrete Ceiling
Wall & Surface Mounting
Hole Dia 20mm to 100mm



SRD SERIES

Wattages
Color Temp
Catalogue Number
Product Weights



Cat. Number	Mounting	Wattage	Lumens	IP Rating	Color Temp	Voltages	Temperature	Weight
CRLED-SRD-RR-9W-3-CCT	Recessed	9W	900	IP20	3K/4K/6K	100-240VAC	-20 to+45	0.22
CRLED-SRD-RR-12W-3-CCT	Recessed	12W	1200	IP20	3K/4K/6K	100-240VAC	-20 to+45	0.38
CRLED-SRD-RR-18W-3-CCT	Recessed	18W	1800	IP20	3K/4K/6K	100-240VAC	-20 to+45	0.82
CRLED-SRD-RR-24W-3-CCT	Recessed	24W	2400	IP20	3K/4K/6K	100-240VAC	-20 to+45	0.97
CRLED-SRD-SR-9W-3-CCT	Surface	9W	900	IP20	3K/4K/6K	100-240VAC	-20 to+45	0.22
CRLED-SRD-SR-12W-3-CCT	Surface	12W	1200	IP20	3K/4K/6K	100-240VAC	-20 to+45	0.38
CRLED-SRD-SR-18W-3-CCT	Surface	18W	1800	IP20	3K/4K/6K	100-240VAC	-20 to+45	0.82
CRLED-SRD-SR-24W-3-CCT	Surface	24W	2400	IP20	3K/4K/6K	100-240VAC	-20 to+45	0.97
CRLED-SRD-RR-9W-6K	Recessed	9W	900	IP20	6000K	100-240VAC	-20 to+45	0.22
CRLED-SRD-RR-12W-6K	Recessed	12W	1200	IP20	6000K	100-240VAC	-20 to+45	0.38
CRLED-SRD-RR-9W-4K	Recessed	9W	900	IP20	4000K	100-240VAC	-20 to+45	0.22
CRLED-SRD-RR-12W-4K	Recessed	12W	1200	IP20	4000K	100-240VAC	-20 to+45	0.38
CRLED-SRD-RR-9W-3K	Recessed	9W	900	IP20	3000K	100-240VAC	-20 to+45	0.22
CRLED-SRD-RR-12W-3K	Recessed	12W	1200	IP20	3000K	100-240VAC	-20 to+45	0.38

Dimensions

Dimensions (mm)	Dia ϕ	H (mm)	Cut Size
Size A (9W)	155	20	70-100 mm
Size B (12W)	175	20	70-120 mm
Size C (18W)	225	20	70-170 mm
Size D (24W)	300	20	70-240 mm